

POWERTECH ENGINES INC.

Central & Northern California Operations: 2933 E Hamilton Ave., Fresno, California 93721

· Phone 559-264-1776 · Toll Free 800-750-1776 · Fax 559-264-2933

Southern California Operations: 1410-B S Acacia Ave., Fullerton, California 92831

· Phone 714-635-1776 · Toll Free 800-784-1776 · Fax 714-635-1771

HQ & Accounting: PO Box 3489, Los Altos, California 94024-0489

· Toll Free 800-944-1776 <http://www.powertechengines.com> · Fax 650-964-3298

MODEL 10 Diesel Prime Power Generator

10.2 kW STANDBY - 9.5 kW PRIME @ 77 F & SEA LEVEL

LOMBARDINI model LDW 1404 FOCS 1372 cc four cylinder diesel engine, rated ~19 gross intermittent HP and ~17 gross continuous HP at 1800 rpm (for 60 Hz operation). This open power unit style generation system includes the engine and radiator, muffler, full overhead control fuel system, air cleaner, blower fan, an engine control panel that includes low oil pressure, high water temperature, safety shut downs and warning lights, key start, battery tray & cables, rubber vibration mounts, assembled together with the generator (see below) on a welded steel frame.

MARATHON or **NEWAGE** or **MECC ALTE** 12 lead or 4 lead generator end. Four lead generator ends are more efficient for 120/240 VAC applications. 12 lead generator ends are very flexible, and can be connected for a variety of applications, including 480 VAC three phase, 240/120 VAC three phase or 120/240 VAC single phase. An AVR voltage regulator is included and will be adjusted by our shop for the winding/voltage configuration specified. These units meet NEMA generator standards and are suitable for prime or standby power. A copy of the generator factory data sheet will be supplied upon request. Many are also posted on our web site.

The Model 10 with a Newage BCI-164-D is approximately 51" long; 27.3" wide, and has a maximum height at the top of the radiator cap of ~31". The top of the engine valve cover is at 27"; it is ~23" to the top of the alternator. Minimum dimensions with a custom skid would be about 21.5" wide, and 47" long, with a maximum height of ~29". It weighs about 680 pounds.

Approximate fuel consumption: at 1/2 load = ~0.57 gal/hour; at full load = ~1.13 gal/hour.

All units are fully assembled and test run under load prior to shipment using our calibrated factory load banks(s) at our Fullerton, CA manufacturing facility.

Options include the following; others maybe available upon special request:

- **Water and oil level safeties.**
- **2 or 3 pole main line circuit breaker.**
- **Oversize alternators for motor starting.**
- **Transfer switches.**
- **Block heaters.**
- **Deluxe control panels with gauges, autostart, and/or with AC metering gauges.**

03/10/03 [Revised]. All specifications are subject to change without notice.